BG-ADAMO-4K

4K@60Hz 12G-SDI/HDMI2.0/USB 2.0/ USB 3.0 Live Streaming PTZ Camera with Tally Lights (Available in black & white)

BZBGEAR is proud to announce the next generation in pan, tilt, and zoom cameras—the BG-ADAMO-4K. With its unique design and exclusive feature set, ADAMO is unrivaled in the live streaming broadcast market.

4K@60Hz resolution over HDMI and 12G-SDI connections simplifies long distance cable runs while maximizing high-quality imagery. A 1 TB microSDXC card writer performs quick setups when other connections are not readily available. Also equipped with variable intensity LED tally lights, ADAMO is a game changer!

Pristine Detail, Accurate Color, Quiet Operation

- Optical zoom lens: 12x (25 ft), 25x (50 ft), 31x (75 ft)
- 4K@60Hz resolutions provide fluid motion, clear image, and accurate colors
- Auto focusing algorithms resulting in quick, accurate, and stable focus

Digital and Analog Control at Your Fingertips

- Web interface control via the IP address; camera preview access
- IR remote control
- Supports IP and serial control protocols (Visca IP, ONVIF / Pelco-P/D, Visca)
- Free BG-PTZ-Control app/program for Apple devices, PCs

Unrivaled Diversity of Connections and Streaming Formats

- Supports RTSP, RTMP, RTMPS, ONVIF, and GB/T28181
- 12G-SDI, HDMI, USB 2.0/3.0, LAN / Power over Ethernet
- H.264/H.265 video compression formats provide excellent image quality
- 3.5 mm input for embedding audio into your live stream

Compatible Live Streaming Software & Online Platforms

- vMix, Wirecast, Echo360, Zoom, Skype, Meet, GoToMeeting, & more
- YouTube, Facebook, Linkedin, Instagram, Twitter, Twitch, & more

FREE Software Control Program
BG-PTZ-CONTROL

Specifications

BG-ADAMO-4K	
HDMI Video Output	3840*2160p@60Hz/50/30/25/59.94/29.97 - 1080p@60Hz/50/30/25/59.94/29.97 1080i@60Hz/50/30/59.94 - 720p@60Hz/50/59.94
12G-SDI Video Output	3840*2160p@60Hz/50/30/25 - 1080p@60Hz/50/30/25 - 720p@60Hz/50
USB 3.0 Video Output	YUY2：1920*1080/1600*896 /1280*720 /1024*576 /960*540 /800*600/800*448 /720*576/720*480/P60/50/30/25; NV12：1920*1080/1600*896 /1280*720 /1024*576 /960*540 /800*600/800*448 /720*576/720*480/P60/50/30/25;
USB 2.0 Video Output	**MJPG:** 3840*2160P30; 1920*1080/1600*896 /1280*720 /1024*576 /960*540 /800*600/800*448 /720*576/720*480/640*480 /640*360 /480*270 /352*288/320*240P60/50/30/25; **H264：** 3840*2160P30; 1920*1080 /1600*896 /1280*720 /1024*576 /960*540 /800*600 /800*448/720*576/720*480/640*480 /640*360 /480*270/352*288/320*240P60/50/30/25; **YUY2：** 640*360 /480*270 /320*180P30/25 **NV12：** 640*480 /640*360 /480*270 /320*180P30/25
LAN Video Output Format	**Main stream：** 3840*2160/5-30fps; 1920*1080/5-60fps; 1280*720/5-60fps **Substream：** 720*480; 640*480; 640*360; 320*240; 320*180/5-30fps
Dimensions (LxWxH)	248 x 191 x 210 mm

AT A GLANCE
Zoom
12x, 25x, 31x Optical Zoom
Video Output(s)
12G-SDI, HDMI, USB 2.0, USB 3.0, IP-LAN
Audio Input(s)
3.5 mm
Control
RS232, RS485, LAN, IR Remote
Power Connections
Power Supply, Power over Ethernet

SUITABLE APPLICATIONS
Business Conference Rooms
Healthcare
Education
Houses of Worship
Live Events

Industry-Leading Warranty & Support

BZBGEAR Pro AV products and Cameras come with a three-year warranty. An extended two-year warranty is available for our Cameras upon registration for a total of five years.

We pride ourselves in our Customer Service and seven-days-a-week Tech Support.

BZBGEAR®
Solutions to Amplify Your World™

830 National Drive, Suite 140
Sacramento, CA 95834

1.888.499.9906
info@bzbgear.com